

Image stitching

Digital Visual Effects
Yung-Yu Chuang


with slides by Richard Szeliski, Steve Seitz, Matthew Brown and Vaclav Hlavac

Image stitching

- Stitching = alignment + blending

↑
geometrical
registration

↑
photometric
registration



Applications of image stitching


- Video stabilization
- Video summarization
- Video compression
- Video matting
- Panorama creation

Video summarization



Video compression

DigiVFX



Object removal


DigiVFX



input video

Object removal

DigiVFX



remove foreground

Object removal

DigiVFX



estimate background

Object removal

DigiVFX



background estimation

Panorama creation

DigiVFX



Why panorama?

DigiVFX


- Are you getting the whole picture?
 - Compact Camera FOV = $50 \times 35^\circ$



Why panorama?

DigiVFX

- Are you getting the whole picture?
 - Compact Camera FOV = $50 \times 35^\circ$
 - Human FOV = $200 \times 135^\circ$



Why panorama?

DigiVFX

- Are you getting the whole picture?
 - Compact Camera FOV = $50 \times 35^\circ$
 - Human FOV = $200 \times 135^\circ$
 - Panoramic Mosaic = $360 \times 180^\circ$



Panorama examples

DigiVFX

- Like HDR, it is a topic of computational photography, seeking ways to build a better camera mostly in software.
- Most consumer cameras have a panorama mode
- Mars:
http://www.panoramas.dk/fullscreen3/f2_mars97.html
- Earth:
<http://www.panoramas.dk/new-year-2006/taipei.html>
<http://www.360cities.net/>


What can be globally aligned?

DigiVFX

- In image stitching, we seek for a matrix to globally warp one image into another. Are any two images of the same scene can be aligned this way?
 - Images captured with the same center of projection
 - A planar scene or far-away scene

A pencil of rays contains all views


DigiVFX



Can generate any synthetic camera view as long as it has **the same center of projection!**

Mosaic as an image reprojection

DigiVFX




- The images are reprojected onto a common plane
- The mosaic is formed on this plane
- Mosaic is a *synthetic wide-angle camera*

Changing camera center


DigiVFX

- Does it still work?



Planar scene (or a faraway one)

DigiVFX




- PP3 is a projection plane of both centers of projection, so we are OK!
- This is how big aerial photographs are made

Motion models

DigiVFX


- Parametric models as the assumptions on the relation between two images.

2D Motion models



Name	Matrix	# D.O.F.	Preserves:	Icon
translation	$\begin{bmatrix} I & t \end{bmatrix}_{2 \times 3}$	2	orientation + ...	
rigid (Euclidean)	$\begin{bmatrix} R & t \end{bmatrix}_{2 \times 3}$	3	lengths + ...	
similarity	$\begin{bmatrix} sR & t \end{bmatrix}_{2 \times 3}$	4	angles + ...	
affine	$\begin{bmatrix} A \end{bmatrix}_{2 \times 3}$	6	parallelism + ...	
projective	$\begin{bmatrix} \tilde{H} \end{bmatrix}_{3 \times 3}$	8	straight lines	

Motion models






Translation

Affine

Perspective

3D rotation



2 unknowns


6 unknowns

8 unknowns

3 unknowns

A case study: cylindrical panorama

- What if you want a 360° field of view?



mosaic projection cylinder

Cylindrical panoramas



- Steps
 - Reproject each image onto a cylinder
 - Blend
 - Output the resulting mosaic

Cylindrical panorama

DigiVFX

1. Take pictures on a tripod (or handheld)
2. Warp to cylindrical coordinate
3. Compute pairwise alignments
4. Fix up the end-to-end alignment
5. Blending
6. Crop the result and import into a viewer

It is required to do radial distortion correction for better stitching results!

Taking pictures

DigiVFX



Kaidan panoramic tripod head

Translation model


DigiVFX



Try to align this in PaintShop Pro


Where should the synthetic camera be

DigiVFX




- The projection plan of some camera
- Onto a cylinder

Cylindrical projection




Adopted from <http://www.cambridgeincolour.com/tutorials/image-projections.htm>

Cylindrical projection




Cylindrical projection




Adopted from <http://www.cambridgeincolour.com/tutorials/image-projections.htm>

Cylindrical projection




$$(\sin \theta, h, \cos \theta) \propto (x, y, f)$$




$$\theta = \tan^{-1} \frac{x}{f}$$

Cylindrical projection



Cylindrical projection



Cylindrical reprojection





Image 384x300

f = 180 (pixels)

f = 280

f = 380

A simple method for estimating f



Or, you can use other software, such as AutoStich, to help.

Input images

DigiVFX



Cylindrical warping

DigiVFX



Blending

DigiVFX

- Why blending: parallax, lens distortion, scene motion, exposure difference

Blending

DigiVFX



Blending

DigiVFX



Blending

DigiVFX



Assembling the panorama


DigiVFX



- Stitch pairs together, blend, then crop


Problem: Drift

DigiVFX



- Error accumulation
 - small errors accumulate over time

Problem: Drift



• Solution

- add another copy of first image at the end
- there are a bunch of ways to solve this problem
 - add displacement of $(y_1 - y_n)/(n - 1)$ to each image after the first
 - compute a global warp: $y' = y + ax$
 - run a big optimization problem, incorporating this constraint
 - best solution, but more complicated
 - known as "bundle adjustment"

End-to-end alignment and crop



Viewer: panorama



example: <http://www.cs.washington.edu/education/courses/cse590ss/01wi/projects/project1/students/dougz/index.html>

Viewer: texture mapped model



example: <http://www.panoramas.dk/>

Cylindrical panorama

1. Take pictures on a tripod (or handheld)
2. Warp to cylindrical coordinate
3. Compute pairwise alignments
4. Fix up the end-to-end alignment
5. Blending
6. Crop the result and import into a viewer

Determine pairwise alignment?

- Feature-based methods: only use feature points to estimate parameters
- We will study the "Recognising panorama" paper published in ICCV 2003
- Run SIFT (or other feature algorithms) for each image, find feature matches.

Determine pairwise alignment

- $p' = Mp$, where M is a transformation matrix, p and p' are feature matches
- It is possible to use more complicated models such as affine or perspective
- For example, assume M is a 2x2 matrix

$$\begin{pmatrix} x' \\ y' \end{pmatrix} = \begin{pmatrix} m_{11} & m_{12} \\ m_{21} & m_{22} \end{pmatrix} \begin{pmatrix} x \\ y \end{pmatrix}$$

- Find M with the least square error

$$\sum_{i=1}^n (Mp - p')^2$$

Determine pairwise alignment

$$\begin{pmatrix} x' \\ y' \end{pmatrix} = \begin{pmatrix} m_{11} & m_{12} \\ m_{21} & m_{22} \end{pmatrix} \begin{pmatrix} x \\ y \end{pmatrix} \quad \begin{aligned} x_1 m_{11} + y_1 m_{12} &= x'_1 \\ x_1 m_{21} + y_1 m_{22} &= y'_1 \end{aligned}$$

- Overdetermined system

$$\begin{pmatrix} x_1 & y_1 & 0 & 0 \\ 0 & 0 & x_1 & y_1 \\ x_2 & y_2 & 0 & 0 \\ \vdots & \vdots & \vdots & \vdots \\ x_n & y_n & 0 & 0 \\ 0 & 0 & x_n & y_n \end{pmatrix} \begin{pmatrix} m_{11} \\ m_{12} \\ m_{21} \\ m_{22} \end{pmatrix} = \begin{pmatrix} x'_1 \\ y'_1 \\ x'_2 \\ \vdots \\ x'_n \\ y'_n \end{pmatrix}$$

Normal equation

Given an overdetermined system

$$\mathbf{Ax} = \mathbf{b}$$

the normal equation is that which minimizes the sum of the square differences between left and right sides

$$\mathbf{A}^T \mathbf{Ax} = \mathbf{A}^T \mathbf{b}$$

Why?

Normal equation

$$E(\mathbf{x}) = (\mathbf{Ax} - \mathbf{b})^2$$

$$\begin{bmatrix} a_{11} & \dots & a_{1m} \\ \vdots & & \vdots \\ \vdots & & \vdots \\ \vdots & & \vdots \\ a_{n1} & \dots & a_{nm} \end{bmatrix} \begin{bmatrix} x_1 \\ \vdots \\ x_m \end{bmatrix} = \begin{bmatrix} b_1 \\ \vdots \\ \vdots \\ b_n \end{bmatrix}$$

$n \times m$, n equations, m variables

Normal equation

$$\mathbf{Ax} - \mathbf{b} = \begin{bmatrix} \sum_{j=1}^m a_{1j}x_j \\ \vdots \\ \sum_{j=1}^m a_{ij}x_j \\ \vdots \\ \sum_{j=1}^m a_{nj}x_j \end{bmatrix} - \begin{bmatrix} b_1 \\ \vdots \\ b_i \\ \vdots \\ b_n \end{bmatrix} = \begin{bmatrix} \left(\sum_{j=1}^m a_{1j}x_j\right) - b_1 \\ \vdots \\ \left(\sum_{j=1}^m a_{ij}x_j\right) - b_i \\ \vdots \\ \left(\sum_{j=1}^m a_{nj}x_j\right) - b_n \end{bmatrix}$$

$$E(\mathbf{x}) = (\mathbf{Ax} - \mathbf{b})^2 = \sum_{i=1}^n \left[\left(\sum_{j=1}^m a_{ij}x_j\right) - b_i \right]^2$$

Normal equation

$$E(\mathbf{x}) = (\mathbf{Ax} - \mathbf{b})^2 = \sum_{i=1}^n \left[\left(\sum_{j=1}^m a_{ij}x_j\right) - b_i \right]^2$$

$$\begin{aligned} 0 = \frac{\partial E}{\partial x_1} &= \sum_{i=1}^n 2 \left[\left(\sum_{j=1}^m a_{ij}x_j\right) - b_i \right] a_{i1} \\ &= 2 \sum_{i=1}^n a_{i1} \sum_{j=1}^m a_{ij}x_j - 2 \sum_{i=1}^n a_{i1}b_i \end{aligned}$$

$$0 = \frac{\partial E}{\partial \mathbf{x}} = 2(\mathbf{A}^T \mathbf{Ax} - \mathbf{A}^T \mathbf{b}) \rightarrow \mathbf{A}^T \mathbf{Ax} = \mathbf{A}^T \mathbf{b}$$

Normal equation

$$\begin{aligned} & (\mathbf{Ax} - \mathbf{b})^2 \\ &= (\mathbf{Ax} - \mathbf{b})^T (\mathbf{Ax} - \mathbf{b}) \\ &= ((\mathbf{Ax})^T - \mathbf{b}^T) (\mathbf{Ax} - \mathbf{b}) \\ &= (\mathbf{x}^T \mathbf{A}^T - \mathbf{b}^T) (\mathbf{Ax} - \mathbf{b}) \\ &= \mathbf{x}^T \mathbf{A}^T \mathbf{Ax} - \mathbf{b}^T \mathbf{Ax} - \mathbf{x}^T \mathbf{A}^T \mathbf{b} + \mathbf{b}^T \mathbf{b} \\ &= \mathbf{x}^T \mathbf{A}^T \mathbf{Ax} - (\mathbf{A}^T \mathbf{b})^T \mathbf{x} - (\mathbf{A}^T \mathbf{b})^T \mathbf{x} + \mathbf{b}^T \mathbf{b} \end{aligned}$$
$$\frac{\partial E}{\partial \mathbf{x}} = 2\mathbf{A}^T \mathbf{Ax} - 2\mathbf{A}^T \mathbf{b}$$

Determine pairwise alignment

- $p' = Mp$, where M is a transformation matrix, p and p' are feature matches
- For translation model, it is easier.

$$E = \sum_{i=1}^n \left[(m_1 + x_i - x'_i)^2 + (m_2 + y_i - y'_i)^2 \right]$$

$$0 = \frac{\partial E}{\partial m_1}$$

- What if the match is false? Avoid impact of outliers.

RANSAC

- RANSAC = Random Sample Consensus
- An algorithm for robust fitting of models in the presence of many data outliers
- Compare to robust statistics
- Given N data points x_i , assume that majority of them are generated from a model with parameters Θ , try to recover Θ .

RANSAC algorithm

- Run k times: ← How many times?
- (1) draw n samples randomly ← How big? Smaller is better
 - (2) fit parameters Θ with these n samples
 - (3) for each of other $N-n$ points, calculate its distance to the fitted model, count the number of inlier points c
- Output Θ with the largest c

How to define?
Depends on the problem.

How to determine k

p : probability of real inliers

P : probability of success after k trials

$$P = 1 - (1 - p^n)^k$$

n samples are all inliers

a failure

failure after k trials

$$k = \frac{\log(1 - P)}{\log(1 - p^n)}$$

for $P=0.99$


n	p	k
3	0.5	35
6	0.6	97
6	0.5	293

Example: line fitting




Example: line fitting

$n=2$




Model fitting




Measure distances

DigiVFX




Count inliers

DigiVFX




Another trial

DigiVFX




The best model

DigiVFX




RANSAC for Homography

DigiVFX




RANSAC for Homography

DigiVFX



RANSAC for Homography

DigiVFX



Applications of panorama in VFX

DigiVFX

- Background plates
- Image-based lighting

Troy (image-based lighting)

DigiVFX



http://www.cgnetworks.com/story_custom.php?story_id=2195&page=4

Spiderman 2 (background plate)

DigiVFX

