Polynomial Space

PSPACE and Games

- Given a boolean expression ϕ in CNF with boolean variables $x_1, x_2, \ldots, x_n$, is it true that $\exists x_1 \forall x_2 \cdots Q_n x_n \phi$?
- This is called **quantified satisfiability** or QSAT.
- This problem is like a two-person game: $\exists$ and $\forall$ are the two players.
- We ask then is there a winning strategy for $\exists$?
- QSAT Is PSPACE-Complete[a]

[a] Stockmeyer and Meyer (1973).

©2006 Prof. Yuh-Dauh Lyuu, National Taiwan University

IP and PSPACE

- We next prove that coNP $\subseteq$ IP.
- Shamir in 1990 proved that IP equals PSPACE using similar ideas (p. 710).

Interactive Proof for Boolean Unsatisfiability

- Like GRAPH NONISOMORPHISM (p. 538), it is not clear how to construct a short certificate for UNSAT.
- But with interaction and randomization, we shall present an interactive proof for UNSAT.
- A 3SAT formula is a conjunction of disjunctions of at most three literals.
- For any unsatisfiable 3SAT formula $\phi(x_1, x_2, \ldots, x_n)$, there is an interactive proof for the fact that it is unsatisfiable.
- Therefore, coNP $\subseteq$ IP.

©2006 Prof. Yuh-Dauh Lyuu, National Taiwan University

Arithmetization of Boolean Formulas

The idea is to arithmetize the boolean formula.

- T $\rightarrow$ positive integer
- F $\rightarrow 0$
- $x_i \rightarrow x_i$
- $\neg x_i \rightarrow 1 - x_i$
- $\vee \rightarrow +$
- $\wedge \rightarrow \times$
- $\phi(x_1, x_2, \ldots, x_n) \rightarrow \Phi(x_1, x_2, \ldots, x_n)$

©2006 Prof. Yuh-Dauh Lyuu, National Taiwan University

The Arithmetized Version

- A boolean formula is transformed into a multivariate polynomial Φ.
- It is easy to verify that ϕ is unsatisfiable if and only if

$$\sum_{x_1=0,1} \sum_{x_2=0,1} \cdots \sum_{x_n=0,1} \Phi(x_1, x_2, \ldots, x_n) = 0.$$

- But the above seems to require exponential time.
- We turn to more intricate methods.

©2006 Prof. Yuh-Dauh Lyuu, National Taiwan University

Choosing the Field

- Suppose ϕ has m clauses of length three each.
- Then $\Phi(x_1, x_2, \ldots, x_n) \leq 3^m$ for any truth assignment $(x_1, x_2, \ldots, x_n)$.
- Because there are at most 2^n truth assignments,

$$\sum_{x_1=0,1} \sum_{x_2=0,1} \cdots \sum_{x_n=0,1} \Phi(x_1, x_2, \ldots, x_n) \leq 2^n 3^m.$$

©2006 Prof. Yuh-Dauh Lyuu, National Taiwan University

Choosing the Field (concluded)

- By choosing a prime $q > 2^n 3^m$ and working modulo this prime, proving unsatisfiability reduces to proving that

$$\sum_{x_1=0,1} \sum_{x_2=0,1} \cdots \sum_{x_n=0,1} \Phi(x_1, x_2, \ldots, x_n) \equiv 0 \bmod q. \quad (11)$$

- Working under a *finite* field allows us to uniformly select a random element in the field.

©2006 Prof. Yuh-Dauh Lyuu, National Taiwan University

Binding Peggy

- Peggy has to find a sequence of polynomials that satisfy a number of restrictions.
- The restrictions are imposed by Victor: After receiving a polynomial from Peggy, Victor sets a new restriction for the next polynomial in the sequence.
- These restrictions guarantee that if ϕ is unsatisfiable, such a sequence can always be found.
- However, if ϕ is not unsatisfiable, any Peggy has only a small probability of finding such a sequence.
  - The probability is taken over Victor's coin tosses.

©2006 Prof. Yuh-Dauh Lyuu, National Taiwan University

The Algorithm

1: Peggy and Victor both arithmetize ϕ to obtain Φ;
2: Peggy picks a prime $q > 2^n 3^m$ and sends it to Victor;
3: Victor rejects and stops if q is not a prime;
4: Victor sets $v_0 = 0$;
5: **for** $i = 1, 2, \ldots, n$ **do**
6: Peggy calculates $P_i^*(z) = \sum_{x_{i+1}=0,1} \cdots \sum_{x_n=0,1} \Phi(r_1, \ldots, r_{i-1}, z, x_{i+1}, \ldots, x_n)$;
7: Peggy sends $P_i^*(z)$ to Victor;
8: Victor rejects and stops if $P_i^*(0) + P_i^*(1) \not\equiv v_{i-1} \bmod q$ or $P_i^*(z)$'s degree exceeds m; $\{P_i^*(z)$ has at most m clauses.$\}$
9: Victor uniformly picks $r_i \in Z_q$ and calculates $v_i = P_i^*(r_i)$;
10: Victor sends r_i to Peggy;
11: **end for**
12: Victor accepts iff $\Phi(r_1, r_2, \ldots, r_n) \equiv v_n \bmod q$;

©2006 Prof. Yuh-Dauh Lyuu, National Taiwan University

Comments

- The following invariant is maintained by the algorithm:

$$P_i^*(0) + P_i^*(1) \equiv P_{i-1}^*(r_{i-1}) \bmod q \tag{12}$$

  for $1 \le i \le n$.

  - $P_i^*(0) + P_i^*(1)$ equals
    $\sum_{x_i=0,1} \cdots \sum_{x_n=0,1} \Phi(r_1, \ldots, r_{i-1}, x_i, x_{i+1}, \ldots, x_n)$
    modulo q.
  - The above equals $P_{i-1}^*(r_{i-1}) \bmod q$ by definition.

©2006 Prof. Yuh-Dauh Lyuu, National Taiwan University

Comments (concluded)

- The computation of $v_1, v_2, \ldots, v_n$ must rely on Peggy's supplied polynomials as Victor does not have the power to carry out the exponential-time calculations.
- But $\Phi(r_1, r_2, \ldots, r_n)$ in Step 12 is computed without relying on Peggy.

©2006 Prof. Yuh-Dauh Lyuu, National Taiwan University

Completeness

- Suppose ϕ is unsatisfiable.
- For $i \geq 1$, by Eq. (12) on p. 688,

$$\begin{aligned} & P_i^*(0) + P_i^*(1) \\ = & \sum_{x_i=0,1} \sum_{x_{i+1}=0,1} \cdots \sum_{x_n=0,1} \Phi(r_1, \ldots, r_{i-1}, x_i, x_{i+1}, \ldots, x_n) \\ = & P_{i-1}^*(r_{i-1}) \\ \equiv & v_{i-1} \bmod q. \end{aligned}$$

Completeness (concluded)

- In particular at $i = 1$, because ϕ is unsatisfiable, we have

$$\begin{aligned} P_1^*(0) + P_1^*(1) &= \sum_{x_1=0,1} \cdots \sum_{x_n=0,1} \Phi(x_1, \ldots, x_n) \\ &\equiv v_0 \\ &= 0 \bmod q. \end{aligned}$$

- Finally, $v_n = P_n^*(r_n) = \Phi(r_1, r_2, \ldots, r_n)$.
- Because all the tests by Victor will pass, Victor will accept ϕ.

©2006 Prof. Yuh-Dauh Lyuu, National Taiwan University

Soundness

- Suppose ϕ is not unsatisfiable.
- Victor will reject after an honest Peggy sends $P_1^*(z)$.
  - $P_1^*(z) = \sum_{x_2=0,1} \cdots \sum_{x_n=0,1} \Phi(z, x_2, \ldots, x_n)$.
  - So

$$\begin{aligned} & P_1^*(0) + P_1^*(1) \\ = & \sum_{x_1=0,1} \sum_{x_2=0,1} \cdots \sum_{x_n=0,1} \Phi(x_1, x_2, \ldots, x_n) \\ \not\equiv & \ 0 \bmod q \end{aligned}$$

    by Eq. (11) on p. 685.
  - But $v_0 = 0$.

Soundness (continued)

- We will show that if Peggy is dishonest in one round (by sending a polynomial other than $P_i^*(z)$), then with high probability she must be dishonest in the next round, too.
- In the last round (Step 12), her dishonesty is exposed.

©2006 Prof. Yuh-Dauh Lyuu, National Taiwan University

Soundness (continued)

- Let $P_i(z)$ represent the polynomial sent by Peggy in place of $P_i^*(z)$.
- Victor calculates $v_i = P_i(r_i) \bmod p$.
- In order to deceive Victor in the next round, round $i+1$, Peggy must use $r_1, r_2, \ldots, r_i$ to find a $P_{i+1}(z)$ of degree at most m such that

$$P_{i+1}(0) + P_{i+1}(1) \equiv v_i \bmod q$$

  (see Step 8 of the algorithm on p. 687).
- And so on to the end, except that Peggy has no control over Step 12.

©2006 Prof. Yuh-Dauh Lyuu, National Taiwan University

A Key Claim

Lemma 88 *If* $P_i^*(0) + P_i^*(1) \not\equiv v_{i-1} \bmod q$, *then either Victor rejects in the* i*th round, or* $P_i^*(r_i) \not\equiv v_i \bmod q$ *with probability at least* $1 - (m/q)$, *where the probability is taken over Victor's choices of* r_i.

- Think of $P_i^*(r_i)$ as the v_i that Victor *should be* computing if Peggy were honest.
- But Victor actually calculates $P_i(z)$ as v_i (Peggy claims $P_i(z)$ is $P_i^*(z)$).
- So $v_i = P_i(r_i) \bmod q$.
- What Victor can do is to check for consistencies.

©2006 Prof. Yuh-Dauh Lyuu, National Taiwan University

The Proof of Lemma 88 (continued)

- If Peggy sends a $P_i(z)$ which equals $P_i^*(z)$, then

$$P_i(0) + P_i(1) = P_i^*(0) + P_i^*(1) \not\equiv v_{i-1} \bmod q,$$

  and Victor rejects immediately.

- Suppose Peggy sends a $P_i(z)$ different from $P_i^*(z)$.

- If $P_i(z)$ does not pass Victor's test

$$P_i(0) + P_i(1) \equiv v_{i-1} \bmod q, \tag{13}$$

  then Victor rejects and we are done, too.

©2006 Prof. Yuh-Dauh Lyuu, National Taiwan University

The Proof of Lemma 88 (concluded)

- Finally, assume $P_i(z)$ passes the test (13).
- $P_i(z) - P_i^*(z) \not\equiv 0$ is a polynomial of degree at most m.
- Hence equation $P_i(z) - P_i^*(z) \equiv 0 \bmod q$ has at most m roots $r \in Z_q$, i.e.,

$$P_i^*(r) \equiv v_i \bmod q.$$

- Hence Victor will pick one of these as his r_i so that

$$P_i^*(r_i) \equiv v_i \bmod q$$

with probability at most m/q.

©2006 Prof. Yuh-Dauh Lyuu, National Taiwan University

Soundness (continued)

- Suppose Victor does not reject in any of the first n rounds.
- As ϕ is not unsatisfiable,

$$P_1^*(0) + P_1^*(1) \not\equiv v_0 \bmod q.$$

- By Lemma 88 (p. 695) and the fact that Victor does not reject, we have $P_1^*(r_1) \not\equiv v_1 \bmod q$ with probability at least $1 - (m/q)$.
- Now by Eq. (12) on p. 688,

$$P_1^*(r_1) = P_2^*(0) + P_2^*(1) \not\equiv v_1 \bmod q.$$

©2006 Prof. Yuh-Dauh Lyuu, National Taiwan University

Soundness (concluded)

- Iterating on this procedure, we eventually arrive at

$$P_n^*(r_n) \not\equiv v_n \bmod q$$

  with probability at least $(1 - m/q)^n$.

- As $P_n^*(r_n) = \Phi(r_1, r_2, \ldots, r_n)$, Victor's last test at Step 12 fails and he rejects.

- Altogether, Victor rejects with probability at least

$$[\, 1 - (m/q) \,]^n > 1 - (nm/q) > 2/3 \qquad (14)$$

  because $q > 2^n 3^m$.

©2006 Prof. Yuh-Dauh Lyuu, National Taiwan University

An Example

- $(x_1 \vee x_2 \vee x_3) \wedge (x_1 \vee \neg x_2 \vee \neg x_3)$.
- The above is satisfied by assigning true to x_1.
- The arithmetized formula is

  $$\Phi(x_1, x_2, x_3) = (x_1 + x_2 + x_3) \times [\, x_1 + (1 - x_2) + (1 - x_3) \,].$$

- Indeed, $\sum_{x_1=0,1} \sum_{x_2=0,1} \sum_{x_3=0,1} \Phi(x_1, x_2, x_3) = 16 \neq 0$.
- We have $n = 3$ and $m = 2$.
- A prime q that satisfies $q > 2^3 \times 3^2 = 72$ is 73.

©2006 Prof. Yuh-Dauh Lyuu, National Taiwan University

An Example (continued)

- The table below is an execution of the algorithm in Z_{73} *when Peggy follows the protocol.*

i	$P_i^*(z)$	$P_i^*(0) + P_i^*(1)$	$= v_{i-1}$?	r_i	v_i
0					0
1	$4z^2 + 8z + 2$	16	no		

- Victor therefore rejects ϕ early on at $i = 1$.

©2006 Prof. Yuh-Dauh Lyuu, National Taiwan University

An Example (continued)

- Now suppose Peggy does not follow the protocol.
- In order to deceive Victor, she comes up with fake polynomials $P_i(z)$ from $i = 1$.
- The table below is an execution of the algorithm.

i	$P_i(z)$	$P_i(0) + P_i(1)$	$= v_{i-1}$?	r_i	v_i
0					0
1	$8z^2 + 11z + 27$	0	yes	2	35
2	$z^2 + 8z + 13$	35	yes	3	46
3	$3z^2 + z + 21$	46	yes	r_3	$P_3(r_3)$

©2006 Prof. Yuh-Dauh Lyuu, National Taiwan University

An Example (concluded)

- Victor has been satisfied up to round 3.
- Finally at Step 12, Victor checks if

$$\Phi(2, 3, r_3) \equiv P_3(r_3) \bmod 73.$$

- It can be verified that the only choices of $r_3 \in \{0, 1, \ldots, 72\}$ that can mislead Victor are 31 and 59.
- The probability of that happening is only $2/73$.[a]

[a] Ms. Ching-Ju Lin (R92922038) on January 7, 2004, pointed out an error in an earlier calculation.

©2006 Prof. Yuh-Dauh Lyuu, National Taiwan University

An Example

- $(x_1 \vee x_2) \wedge (x_1 \vee \neg x_2) \wedge (\neg x_1 \vee x_2) \wedge (\neg x_1 \vee \neg x_2)$.
- The above is unsatisfiable.
- The arithmetized formula is

  $$\Phi(x_1, x_2) = (x_1 + x_2) \times (x_1 + 1 - x_2) \times (1 - x_1 + x_2) \times (2 - x_1 - x_2).$$

- Because $\Phi(x_1, x_2) = 0$ for any *boolean* assignment $\{ 0, 1 \}^2$ to (x_1, x_2), certainly

  $$\sum_{x_1=0,1} \sum_{x_2=0,1} \Phi(x_1, x_2) = 0.$$

- With $n = 2$ and $m = 4$, a prime q that satisfies $q > 2^2 \times 3^4 = 4 \times 81 = 324$ is 331.

©2006 Prof. Yuh-Dauh Lyuu, National Taiwan University

An Example (concluded)

- The table below is an execution of the algorithm in Z_{331}.

i	$P_i^*(z)$	$P_i^*(0) + P_i^*(1)$	$= v_{i-1}$?	r_i	v_i
0					0
1	$z(z+1)(1-z)(2-z)$ $+(z+1)z(2-z)(1-z)$	0	yes	10	283
2	$(10+z) \times (11-z)$ $\times(-9+z) \times (-8-z)$	283	yes	5	46

- Victor calculates $\Phi(10, 5) \equiv 46 \bmod 331$.
- As it equals $v_2 = 46$, Victor accepts ϕ as unsatisfiable.

©2006 Prof. Yuh-Dauh Lyuu, National Taiwan University

Objections to the Soundness Proof?[a]

- Based on the steps required of a cheating Peggy on p. 694, why must we go through so many rounds (in fact, n rounds)?
- Why not just go directly to round n:
  - Victor sends $r_1, r_2, \ldots, r_{n-1}$ to Peggy.
  - Peggy returns with a (claimed) $P_n^*(z)$.
  - Victor accepts if and only if $\Phi(r_1, r_2, \ldots, r_{n-1}, r_n) \equiv P_n^*(r_n) \bmod q$ for a random $r_n \in Z_q$.

[a]Contributed by Ms. Emily Hou (D89011) and Mr. Pai-Hsuen Chen (R90008) on January 2, 2002.

©2006 Prof. Yuh-Dauh Lyuu, National Taiwan University

Objections to the Soundness Proof? (continued)

- Let us analyze the compressed proposal when ϕ is satisfiable.
- To succeed in foiling Victor, Peggy must find a polynomial $P_n(z)$ of degree m such that

$$\Phi(r_1, r_2, \ldots, r_{n-1}, z) \equiv P_n(z) \bmod q.$$

- But this she is able to do: Just give the verifier the polynomial $\Phi(r_1, r_2, \ldots, r_{n-1}, z)$!
- What has happened?

©2006 Prof. Yuh-Dauh Lyuu, National Taiwan University

Objections to the Soundness Proof? (concluded)

- You need the intermediate rounds to "tie" Peggy up with a chain of claims.
- In the original algorithm on p. 687, for example, $P_n(z)$ is bound by the equality $P_n(0) + P_n(1) \equiv v_{n-1} \bmod q$ in Step 8.
- That v_{n-1} is in turn derived by an earlier polynomial $P_{n-1}(z)$, which is in turn bound by $P_{n-1}(0) + P_{n-1}(1) \equiv v_{n-2} \bmod q$, and so on.

©2006 Prof. Yuh-Dauh Lyuu, National Taiwan University

Shamir's Theorem[a]

Theorem 89 *IP = PSPACE.*

- We first sketch the proof for IP $\subseteq$ PSPACE.
- Without loss of generality, assume:
  - If $x \in L$, then the probability that x is accepted by the verifier is at least 3/4.
  - If $x \notin L$, then the probability that x is accepted by the verifier with *any* prover is at most 1/4.

[a]Shamir (1990).

The Proof (continued)

- Now we track down every possible message exchange based on random choices by the verifier and all possible messages generated by the prover.
- Use recursion to calculate

$$\text{prob}[\,\text{verifier accepts } x\,] = \max_P \text{prob}[\,(V,P) \text{ accepts } x\,].$$

- If this value is at least $3/4$, then $x \in L$; otherwise, $x \notin L$.

The Proof (continued)

- To prove PSPACE $\subseteq$ IP, we next prove that QSAT is in IP.
- We do so by describing an interactive protocol that decides QSAT.
- Suppose Alice and Bob are given

$$\begin{aligned}\phi &= \forall x \exists y (x \vee y) \wedge \forall z [\, (x \wedge z) \vee (y \wedge \neg z) \,] \\ &\quad \vee \exists w [\, z \vee (y \wedge \neg w) \,].\end{aligned}$$

- As above, we assume no occurrence of a variable is separated by more than one $\forall$ from its point of quantification.

Proof of Theorem (continued)

- We also assume that $\neg$ is applied only to variables, not subexpressions.
- We now arithmetize ϕ as before except:
  - 1 means true.
  - $\neg x \to 1 - x$.
    - It is the standard representation on p. 134.
  - $\exists x \to \sum_{x=0,1}$.
  - $\forall x \to \prod_{x=0,1}$.
- Alice tries to convince Bob that this arithmetization of ϕ is nonzero.

Proof of Theorem (continued)

- Our ϕ becomes

$$A_\phi = \prod_{x=0}^{1} \sum_{y=0}^{1} \{(x+y) \cdot \prod_{z=0}^{1} [(x \cdot z + y \cdot (1-z)) + \sum_{w=0}^{1} (z + y \cdot (1-w))]\}.$$

- Call it a $\sum - \prod$ expression.
- A_ϕ is a number; it equals 96 here.

©2006 Prof. Yuh-Dauh Lyuu, National Taiwan University

Proof of Theorem (continued)

- As before, ϕ is true if and only if $A_\phi > 0$.
- In fact, more is true.
- For any ϕ and any truth assignment to its free variables:
  - If ϕ is true, then $A_\phi > 0$ under the corresponding 0-1 assignment.
  - If ϕ is false, then $A_\phi = 0$.
- So Alice only has to convince Bob that $A_\phi > 0$.

©2006 Prof. Yuh-Dauh Lyuu, National Taiwan University

Proof of Theorem (continued)

- The trouble is that A_ϕ evaluated can be exponential in length.
- Fortunately, it can be shown that if expression A_ϕ of length n is nonzero, then there is a prime p between 2^n and 2^{3n} such that $A_\phi \neq 0 \bmod p$.
- So Alice only has to convince Bob that $A_\phi \neq 0$ under mod$p$.
- The protocol starts with Alice sending Bob p (assume $p = 13$) and its primality certificate.

Proof of Theorem (continued)

- Now Alice sends Bob A_ϕ mod p, which is

$$\boldsymbol{a} = 96 \bmod 13 = 5.$$

- Each stage starts with the following:
  - A $\sum - \prod$ expression A, with a leading $\sum_x$ or $\prod_x$.
  - A's alleged value a mod p, supplied by Alice.
- If the first $\sum$ or $\prod$ is deleted, the result is a polynomial in x, called $A'(x)$.
- Bob demands from Alice the coefficients of $A'(x)$.
- Trouble occurs if the degree of $A'(x)$ is exponential in n.

©2006 Prof. Yuh-Dauh Lyuu, National Taiwan University

Proof of Theorem (continued)

- Luckily, $\deg(A'(x)) \leq 2n$.
  - No occurrence of a variable is separated by more than one $\forall$ from its point of quantification.
  - So $A'(x)$ has only one $\prod$ symbol.
  - Other $\prod$s are over quantities not related to x, hence purely numerical.
  - Symbols other than $\prod$ can only increase the degree of $A'(x)$ by at most one.
  - For example, $\sum_y (x + y) \prod_z (x + \sum_w (x \cdot w))$.
- So Alice has no problem transmitting $A'(x)$ to Bob.

©2006 Prof. Yuh-Dauh Lyuu, National Taiwan University