




Applied Deep Learning



Transformer



October 5th, 2023 <http://adl.miulab.tw>



**National
Taiwan
University**
國立臺灣大學

2

Sequence Encoding

Basic Attention


Representations of Variable Length Data

- ◉ Input: word sequence, image pixels, audio signal, click logs
- ◉ Property: continuity, temporal, importance distribution
- ◉ Example
 - ✓ Basic combination: average, sum
 - ✓ Neural combination: network architectures should consider input domain properties
 - CNN (convolutional neural network)
 - RNN (recurrent neural network): temporal information

Network architectures should consider the input domain properties


4 Recurrent Neural Networks

- Learning variable-length representations
 - ✓ Fit for sentences and sequences of values
- Sequential computation makes parallelization difficult
- No explicit modeling of long and short range dependencies




Convolutional Neural Networks

- Easy to parallelize
- Exploit local dependencies
 - ✓ **Long-distance** dependencies require many layers





Attention

- Encoder-decoder model is important in NMT
- RNNs need **attention mechanism** to handle long dependencies
- Attention allows us to access any state



7

Basic Attention



Dot-Product Attention

- Input: a query q and a set of key-value (k - v) pairs to an output
- Output: weighted sum of values

Inner product of
query and corresponding key

$$A(q, K, V) = \sum_i \frac{\exp(q \cdot k_i)}{\sum_j \exp(q \cdot k_j)} v_i$$

- ✓ Query q is a d_k -dim vector
- ✓ Key k is a d_k -dim vector
- ✓ Value v is a d_v -dim vector

Dot-Product Attention in Matrix



- Input: *multiple* queries q and a set of key-value (k - v) pairs to an output
- Output: a set of weighted sum of values

$$A(q, K, V) = \sum_i \frac{\exp(q \cdot k_i)}{\sum_j \exp(q \cdot k_j)} v_i$$

$$A(Q, K, V) = \text{softmax}(QK^T)V$$

$$[|Q| \times d_k] \times [d_k \times |K|] \times [|K| \times d_v]$$

softmax
row-wise



$$= [|Q| \times d_v]$$

10

Sequence Encoding


Self-Attention

- Encoder-decoder model is important in NMT
- RNNs need **attention mechanism** to handle long dependencies
- Attention allows us to access any state

Using attention to replace recurrence architectures


Self-Attention

- Constant “path length” between two positions
- Easy to parallelize



Self-Attention


- Constant “path length” between two positions
- Easy to parallelize




Can be either **input** or a **hidden layer**

Self-Attention

- Constant “path length” between two positions
- Easy to parallelize




Self-Attention



Self-Attention

$$\alpha'_{1,i} = e^{\alpha_{1,i}} / \sum_j e^{\alpha_{1,j}}$$



$$q^1 = W^q a^1$$

$$k^1 = W^k a^1$$

$$k^2 = W^k a^2$$


$$k^3 = W^k a^3$$

$$k^4 = W^k a^4$$


Self-Attention

extract information based
on attention scores

$$b^1 = \sum_i \alpha'_{1,i} v^i$$




Self-Attention



Can be either **input** or a **hidden layer**

Self-Attention

$$b^2 = \sum_i \alpha'_{2,i} v^i$$



Self-Attention

$$q^i = W^q a^i$$

q^1
 q^2
 q^3
 q^4

$=$

W^q
 a^1
 a^2
 a^3
 a^4

Q

I

$$k^i = W^k a^i$$

k^1
 k^2
 k^3
 k^4

$=$

W^k
 a^1
 a^2
 a^3
 a^4

K

I

$$v^i = W^v a^i$$





v^1
 v^2
 v^3
 v^4

$=$

W^v
 a^1
 a^2
 a^3
 a^4

V

I



Self-Attention


$$\begin{aligned} \alpha_{1,1} &= k^1 q^1 & \alpha_{1,2} &= k^2 q^1 \\ \alpha_{1,3} &= k^3 q^1 & \alpha_{1,4} &= k^4 q^1 \end{aligned}$$

$\alpha_{1,1}$
 $\alpha_{1,2}$
 $\alpha_{1,3}$
 $\alpha_{1,4}$

=

k^1
 k^2
 k^3
 k^4

q^1



$\alpha'_{1,1}$
 $\alpha'_{1,2}$
 $\alpha'_{1,3}$
 $\alpha'_{1,4}$

$\alpha'_{2,1}$
 $\alpha'_{2,2}$
 $\alpha'_{2,3}$
 $\alpha'_{2,4}$

$\alpha'_{3,1}$
 $\alpha'_{3,2}$
 $\alpha'_{3,3}$
 $\alpha'_{3,4}$

$\alpha'_{4,1}$
 $\alpha'_{4,2}$
 $\alpha'_{4,3}$
 $\alpha'_{4,4}$

A'

$\alpha_{1,1}$
 $\alpha_{1,2}$
 $\alpha_{1,3}$
 $\alpha_{1,4}$

$\alpha_{2,1}$
 $\alpha_{2,2}$
 $\alpha_{2,3}$
 $\alpha_{2,4}$

$\alpha_{3,1}$
 $\alpha_{3,2}$
 $\alpha_{3,3}$
 $\alpha_{3,4}$

$\alpha_{4,1}$
 $\alpha_{4,2}$
 $\alpha_{4,3}$
 $\alpha_{4,4}$

A


=

k^1
 k^2
 k^3
 k^4

q^1
 q^2
 q^3
 q^4

K^T
 Q

Self-Attention



Self-Attention


$$\begin{aligned} Q &= W^q I \\ K &= W^k I \\ V &= W^v I \end{aligned}$$

Parameters
to be learned


$$\begin{aligned} A' &\leftarrow A = K^T Q \\ O &= V A' \end{aligned}$$

Attention Matrix


Transformer Idea



Encoder Self-Attention (Vaswani+, 2017)



Decoder Self-Attention (Vaswani+, 2017)




27


Sequence Encoding

Multi-Head Attention


Convolutions




Self-Attention




Attention Head: who




Attention Head: did what



Attention Head: to whom




Multi-Head Attention



Comparison


- Convolution: different linear transformations by relative positions




- Attention: a weighted average



- Multi-Head Attention: parallel attention layers with different linear transformations on input/output




Multi-Head Attention



Multi-Head Attention


$$q^{i,1} = W^{q,1} q^i$$

$$q^{i,2} = W^{q,2} q^i$$



Multi-Head Attention

$$b^i = W^O \begin{bmatrix} b^{i,1} \\ b^{i,2} \end{bmatrix}$$




38

Sequence Encoding Transformer




Transformer Overview

- Non-recurrent encoder-decoder for MT
- PyTorch explanation by Sasha Rush
<http://nlp.seas.harvard.edu/2018/04/03/attention.html>



Transformer Overview

- Non-recurrent encoder-decoder for MT
- PyTorch explanation by Sasha Rush
<http://nlp.seas.harvard.edu/2018/04/03/attention.html>




Multi-Head Attention

- Idea: allow words to interact with one another
- Model
 - Map V , K , Q to lower dimensional spaces
 - Apply attention, concatenate outputs
 - Linear transformation

$\text{MultiHead}(Q, K, V)$

$$= \text{Concat}(\text{head}_1, \dots, \text{head}_h) W^O$$


$$\text{head}_i = \text{Attention}(QW_i^Q, KW_i^K, VW_i^V)$$



Scaled Dot-Product Attention


- Problem: when d_k gets large, the variance of $q^T k$ increases
 - q and k are random variables with mean 0 and variance 1
 - $q^T k$ has mean 0 and variance d_k
 - variance 1 is preferred
- Solution: scale by $\sqrt{d_k}$

$$A(Q, K, V) = \text{softmax}\left(\frac{QK^T}{\sqrt{d_k}}\right)V$$



Transformer Overview


- Non-recurrent encoder-decoder for MT
- PyTorch explanation by Sasha Rush
<http://nlp.seas.harvard.edu/2018/04/03/attention.html>



Transformer Encoder Block

- Each block has
 - multi-head attention
 - 2-layer feed-forward NN (w/ ReLU)
- Both parts contain
 - Residual connection
 - Layer normalization (LayerNorm)


$$H(x) = g(x) = x + F(x)$$



Change input to have 0 mean and 1 variance per layer & per training point


→ LayerNorm(x + sublayer(x))

$$\mu^l = \frac{1}{H} \sum_{i=1}^H a_i^l \quad \sigma^l = \sqrt{\frac{1}{H} \sum_{i=1}^H (a_i^l - \mu^l)^2} \quad h_i = f\left(\frac{g_i}{\sigma_i} (a_i - \mu_i) + b_i\right)$$



Encoder Input

- Problem: temporal information is missing
- Solution: **positional encoding** allows words at different locations to have different embeddings with fixed dimensions



Positional Encoding

- Criteria for positional encoding
 - Unique encoding for each position
 - Deterministic
 - Distance between neighboring positions should be the same
 - Model can easily generalize to longer sentences



Positional Encoding

- Criteria for positional encoding
 - ✓ Unique encoding for each position
 - ✓ Deterministic
 - ✓ Distance between neighboring positions should be the same
 - Model can easily generalize to longer sentences
- Idea 1: $PE(pos) = pos$
 - A value to indicate the word's position
 - Larger value (longer sentence) may not be easily generalized ☹️



Positional Encoding

- Criteria for positional embeddings
 - ✓ Unique encoding for each position
 - ✓ Deterministic
 - ✓ Distance between neighboring positions should be the same
 - Model can easily generalize to longer sentences
- Idea 2: 1-hot encoding
 - A d-dim vector to encode d positions
 - Cannot generalize to longer sentences 😞


$[1, 0, 0, \dots, 0]$ \Rightarrow only represent the sequences with the length $\leq d$
 $\underbrace{\hspace{1.5cm}}_{\text{d-dim}}$




Positional Encoding

- Criteria for positional encoding
 - ✓ Unique encoding for each position
 - ✓ Deterministic
 - Distance between neighboring positions should be the same
 - ✓ Model can easily generalize to longer sentences

- Idea 3: $PE(pos) = \frac{pos}{len}$
 - The normalized value of the position (0~1)
 - Distances may differ in sentences with different lengths ☹

	w_1	w_2	w_3	w_4
PE	0.25	0.50	0.75	1.00
				
	0.25			

	w_1	w_2	w_3	w_4	\cdots	w_{10}
PE	0.10	0.20	0.30	0.40		1.00
						
	0.10					




Sinusoidal Positional Encoding

- Criteria for positional embeddings
 - ✓ Unique encoding for each position
 - ✓ Deterministic
 - ✓ Distance between neighboring positions should be the same
 - ✓ Model can easily generalize to longer sentences
- Idea:
$$\text{PE}(\text{pos}, 2i) = \sin\left(\frac{\text{pos}}{100000^{2i/d}}\right)$$
$$\text{PE}(\text{pos}, 2i + 1) = \cos\left(\frac{\text{pos}}{100000^{2i/d}}\right)$$
 - A d-dim vector to represent positions




Sinusoidal Positional Encoding



Sinusoidal Positional Encoding

- Distance between neighboring positions
 - symmetrical
 - decay nicely with time




Dot product of position embeddings for all time-steps



Encoder Input

- Problem: temporal information is missing
- Solution: **positional encoding** allows words at different locations to have different embeddings with fixed dimensions



Multi-Head Attention Details

encoder self attention



1. Multi-head Attention
 2. **Q**uery=**K**ey=**V**alue

decoder self attention

1. **M**asked Multi-head Attention
 2. **Q**uery=**K**ey=**V**alue

encoder-decoder attention

1. Multi-head Attention
 2. Encoder Self attention=**K**ey=**V**alue
 3. Decoder Self attention=**Q**uery



Training Tips

- Byte-pair encodings (BPE)
- Checkpoint averaging
- ADAM optimizer with learning rate changes
- Dropout during training at every layer just before adding residual
- Label smoothing
- Auto-regressive decoding with beam search and length penalties



MT Experiments

Model	BLEU		Training Cost (FLOPs)	
	EN-DE	EN-FR	EN-DE	EN-FR
ByteNet [18]	23.75			
Deep-Att + PosUnk [39]		39.2		$1.0 \cdot 10^{20}$
GNMT + RL [38]	24.6	39.92	$2.3 \cdot 10^{19}$	$1.4 \cdot 10^{20}$
ConvS2S [9]	25.16	40.46	$9.6 \cdot 10^{18}$	$1.5 \cdot 10^{20}$
MoE [32]	26.03	40.56	$2.0 \cdot 10^{19}$	$1.2 \cdot 10^{20}$
Deep-Att + PosUnk Ensemble [39]		40.4		$8.0 \cdot 10^{20}$
GNMT + RL Ensemble [38]	26.30	41.16	$1.8 \cdot 10^{20}$	$1.1 \cdot 10^{21}$
ConvS2S Ensemble [9]	26.36	41.29	$7.7 \cdot 10^{19}$	$1.2 \cdot 10^{21}$
Transformer (base model)	27.3	38.1	$3.3 \cdot 10^{18}$	
Transformer (big)	28.4	41.8	$2.3 \cdot 10^{19}$	



Parsing Experiments

Parser	Training	WSJ 23 F1
Vinyals & Kaiser et al. (2014) [37]	WSJ only, discriminative	88.3
Petrov et al. (2006) [29]	WSJ only, discriminative	90.4
Zhu et al. (2013) [40]	WSJ only, discriminative	90.4
Dyer et al. (2016) [8]	WSJ only, discriminative	91.7
Transformer (4 layers)	WSJ only, discriminative	91.3
Zhu et al. (2013) [40]	semi-supervised	91.3
Huang & Harper (2009) [14]	semi-supervised	91.3
McClosky et al. (2006) [26]	semi-supervised	92.1
Vinyals & Kaiser et al. (2014) [37]	semi-supervised	92.1
Transformer (4 layers)	semi-supervised	92.7
Luong et al. (2015) [23]	multi-task	93.0
Dyer et al. (2016) [8]	generative	93.3



Concluding Remarks

- **Non-recurrence** model is easy to parallelize
- **Multi-head attention** captures different aspects by interacting between words
- **Positional encoding** captures location information
- Each transformer block can be applied to diverse tasks

